## EUROPEAN PAIENT OFFICE

## **Patent Abstracts of Japan**

PUBLICATION NUMBER

09026177

**PUBLICATION DATE** 

28-01-97

APPLICATION DATE

13-07-95

APPLICATION NUMBER

07177117

APPLICANT: TAKUMA CO LTD;

INVENTOR: IRIE NAOKI;


INT.CL.

F24F 7/06 F01N 1/24 F02M 35/14

TITLE

SILENCER HAVING GAS PURIFYING

**FUNCTION** 



ABSTRACT: PROBLEM TO BE SOLVED: To improve the performance of a clean room considering environmental preservation while streamlining air conditioning equipment of the clean room by mounting a sound-absorbing material using an ion exchange fiber in a passage of a gas.

> SOLUTION: A sound absorbing material is formed into a cylindrical body 9 to be packed into a vessel 11 in a regular fashion or at random so that a gas can pass therethrough. The vessel 11 is mounted in a passage of a gas of the apparatus. Further effect is obtained by lining the internal wall of the vessel 11 with a sound absorbing material 10 beforehand. The sound absorbing materials 9 and 10 are used by forming an unwoven cloth with metsuke of 1000-2500g/m<sup>2</sup> and a thickness of 5mm or more while a mixing ratio of an ion exchanger fiber is at least 70wt.%. Moreover, the ion exchange fiber is mixed with a thermoplastic binder fiber to compose the sound absorbing materials 9 and 10 while gas contact surfaces of the sound absorbing materials 9 and 10 undergo a heating treatment to melt a part of the binder fiber thereby enhancing silencing effect and gas purifying effect.

COPYRIGHT: (C)1997,JPO

## XP-002212377

AN - 1997-150575 [14]

AP - JP19950177117 19950713

CPY - KYUN

- TAKU

DC - Q51 Q53 Q74 U11

FS - GMPI:EPI

IC - F01N1/24; F02M35/14; F24F7/06

MC - U11-C15B1

PA - (KYUN) NEC KYUSHU LTD

- (TAKU ) TAKUMA KK

PN - JP9026177 A 19970128 DW199714 F24F7/06 006pp

PR - JP19950177117 19950713

XIC - F01N-001/24; F02M-035/14; F24F-007/06

XP - N1997-124393

AB - J09026177 The silencer is mounted at a gas channel (8) and made from an ion-exchange fibre which consists of a sound absorption material. The gas flowing at a cyclic duct is cleaned through the gas contamination removal function of the ion-exchange fibre that performs sound absorption.

- ADVANTAGE - Achieves compact size thus ensures high quality. Provides enough installation space since silencer and gas appts. are combined.

- (Dwg.2/5)

IW - SILENCER GAS CLEAN FUNCTION BLOW COMPRESSOR ION EXCHANGE FIBRE CONSIST SOUND ABSORB MATERIAL PERFORMANCE GAS CONTAMINATE REMOVE CYCLIC DUCT

IKW - SILENCER GAS CLEAN FUNCTION BLOW COMPRESSOR ION EXCHANGE FIBRE CONSIS SOUND ABSORB MATERIAL PERFORMANCE GAS CONTAMINATE REMOVE CYCLIC DUCT

NC - 001

OPD - 1995-07-13

ORD - 1997-01-28

PAW - (KYUN) NEC KYUSHU LTD

- (TAKU ) TAKUMA KK

TI - Silencer with gas cleaning function for e.g. blower, compressor - has ion-exchange fibre which consists of sound absorption material, that performs gas contamination removal at cyclic duct